

Report No.:

Test Time: 2025-09-16 15:44

## Luminaire Property

Luminaire Manufacturer:

Luminaire Description: 60D

Luminous Width (mm): -14

Current: 0.112 A

Power Factor: 0.858

Luminous Length (mm): -380

Voltage: 230.4 V

Power: 22.10 W

## Photometric Results

CIE Class: Direct

Measurement Flux: 1644.1 lm

Downward Ratio: 100%

Horizontal Diffuse Angle(50%): H49.8

Vertical Diffuse Angle(50%): V49.8

Luminaire Efficacy Rating (LER): 74.44

Max. Intensity: 2518.81 cd

S/MH(C0/C180): 0.82

Total Rated Lamp Lumens: 1644.1 lm

Efficiency: 100%


Upward Ratio: 0%

Central Intensity: 2439.64 cd


Pos of Max. Intensity: H180 V7

S/MH(C90/C270): 0.82

Picture Of Luminaire



Luminous Intensity Distribution Curve



— C0-C180 — C90-C270

C Plane (°):0.0-180.0: 180.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:1.0

Test Device: CHL-6E


Distance: 2.905 m

Humidity:

Inspector:



## Luminous Intensity Distribution Curve




C Plane (°):0.0-180.0: 180.0  
Test Lab:  
Test Type: TYPE C  
Temperature:  
Operator:

Gamma Plane (°):0.0-90.0:1.0  
Test Device: CHL-6E  
Distance: 2.905 m  
Humidity:  
Inspector:



## Luminous Intensity Distribution Curve(cd/klm)




C Plane (°):0.0-180.0: 180.0  
Test Lab:  
Test Type: TYPE C  
Temperature:  
Operator:

Gamma Plane (°):0.0-90.0:1.0  
Test Device: CHL-6E  
Distance: 2.905 m  
Humidity:  
Inspector:



## Isocandela (rectangle)



Imax (100%): 2519 cd

( 10%): 252 cd	( 16%): 403 cd
( 25%): 630 cd	( 40%): 1008 cd
( 63%): 1587 cd	(100%): 2519 cd

C Plane (°):0.0-180.0: 180.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:1.0

Test Device: CHL-6E


Distance: 2.905 m

Humidity:

Inspector:



## IsoLux Plot



Mounting Height: 10.0m    Max Lux(100%): 24.8 lx


— ( 1%): 0.2 lx	— ( 2%): 0.5 lx
— ( 5%): 1.2 lx	— ( 10%): 2.5 lx
— ( 20%): 5.0 lx	— ( 50%): 12.4 lx
— (100%): 24.8 lx	

C Plane (°):0.0-180.0: 180.0  
Test Lab:  
Test Type: TYPE C  
Temperature:  
Operator:

Gamma Plane (°):0.0-90.0:1.0  
Test Device: CHL-6E  
Distance: 2.905 m  
Humidity:  
Inspector:




## Illuminance at a Distance





## Vertical IsoLux Plot



Lowest(m): 1.0m    Highest(m): 11.0m    Max Lux: 2439.6 lx

( 1%): 24.4 lx	( 2%): 48.8 lx
( 5%): 122.0 lx	( 10%): 244.0 lx
( 20%): 487.9 lx	( 50%): 1219.8 lx
(100%): 2439.6 lx	

C Plane (°): 0.0-180.0: 180.0  
Test Lab:  
Test Type: TYPE C  
Temperature:  
Operator:

Gamma Plane (°): 0.0-90.0: 1.0  
Test Device: CHL-6E  
Distance: 2.905 m  
Humidity:  
Inspector:



## Area Flux Table

Unit: lm


Vertical plane		-90	-80	-70	-60	-50	-40	-30	-20	-10	0	10	20	30	40	50	60	70	80	90
Flux(E)	Flux(T)	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
0.0	0.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
0.0	1.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
0.0	4.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
0.0	8.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
11.7	28.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
121.5	134.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
271.4	282.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
358.5	368.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
535.2	365.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
264.6	275.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
115.8	128.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
13.3	30.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
0.0	8.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
0.0	4.3	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
0.0	2.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
0.0	0.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
0.0	1644	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
1512		0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

C Plane (°):0.0-180.0: 180.0  
Test Lab:  
Test Type: TYPE C  
Temperature:  
Operator:

Gamma Plane (°):0.0-90.0:1.0  
Test Device: CHL-6E  
Distance: 2.905 m  
Humidity:  
Inspector:



## The Average Illuminance Effective Figure



C Plane (°): 0.0-180.0: 180.0  
Test Lab:  
Test Type: TYPE C  
Temperature:  
Operator:

Gamma Plane (°): 0.0-90.0: 1.0  
Test Device: CHL-6E  
Distance: 2.905 m  
Humidity:  
Inspector:



## UGR Table

Reflectance:										
Ceiling (cavity)	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
X=2H Y=2H	17.1	17.9	17.3	18.1	18.3	16.9	17.7	17.2	17.9	18.1
3H	17.4	18.1	17.6	18.3	18.6	17.2	17.9	17.5	18.2	18.4
4H	17.4	18.1	17.7	18.4	18.6	17.3	17.9	17.6	18.2	18.5
6H	17.5	18.1	17.8	18.4	18.7	17.3	17.9	17.6	18.2	18.5
8H	17.4	18.0	17.8	18.3	18.6	17.2	17.8	17.6	18.1	18.4
12H	17.4	18.0	17.8	18.3	18.6	17.2	17.8	17.6	18.1	18.4
X=4H Y=2H	17.1	17.8	17.4	18.0	18.3	17.0	17.6	17.3	17.9	18.2
3H	17.5	18.1	17.8	18.4	18.7	17.3	17.9	17.7	18.2	18.5
4H	17.6	18.1	18.0	18.5	18.8	17.5	18.0	17.8	18.3	18.7
6H	17.7	18.1	18.1	18.5	18.9	17.5	17.9	17.9	18.3	18.7
8H	17.7	18.1	18.1	18.5	18.9	17.5	17.9	17.9	18.3	18.7
12H	17.6	18.0	18.1	18.4	18.8	17.4	17.8	17.9	18.2	18.7
X=8H Y=4H	17.6	18.0	18.0	18.4	18.8	17.4	17.9	17.9	18.2	18.7
6H	17.7	18.0	18.1	18.4	18.9	17.5	17.8	18.0	18.3	18.7
8H	17.7	18.0	18.2	18.4	18.9	17.5	17.8	18.0	18.2	18.7
12H	17.7	17.9	18.2	18.4	18.9	17.5	17.7	18.0	18.2	18.7
X=12H Y=4H	17.6	17.9	18.0	18.4	18.8	17.4	17.8	17.8	18.2	18.6
6H	17.7	18.0	18.1	18.4	18.9	17.5	17.8	17.9	18.2	18.7
8H	17.7	17.9	18.1	18.4	18.9	17.5	17.7	18.0	18.2	18.7
Variations with the observer position at spacings:										
S=1.0H	+4.4/-2.7					+4.4/-2.8				
S=1.5H	+6.9/-3.1					+6.9/-3.2				
S=2.0H	+8.8/-3.5					+8.8/-3.7				

Calculate in accordance with CIE Pub.117. The table is revised with  $1644\text{lm}$  ( $8\log(F/F_0) = 1.7$ ).

C Plane (°):0.0-180.0: 180.0  
Test Lab:  
Test Type: TYPE C  
Temperature:  
Operator:

Gamma Plane (°):0.0-90.0:1.0  
Test Device: CHL-6E  
Distance: 2.905 m  
Humidity:  
Inspector:



**FLUX DISTRIBUTION TABLE BASED ON THE IESNA LUMINAIRE CLASSIFICATION SYSTEM**

	ZONE	LUMENS	% LAMP LUMENS
	FORWARD LIGHT	816	49.6
	FL ( 0°-30°)	686	41.7
	FM (30°-60°)	118	7.2
	FH (60°-80°)	11	0.7
	FVH (80°-90°)	1	0.0
	BACK LIGHT	828	50.4
	BL ( 0°-30°)	704	42.8
	BM (30°-60°)	114	6.9
	BH (60°-80°)	10	0.6
	BVH (80°-90°)	1	0.0
	UP LIGHT	0	0.0
	UL (90°-100°)	0	0.0
	UH (100°-180°)	0	0.0
	TRAPPED LIGHT	NA	NA

BUG(Backlight,Uplight,Glare) Rating Base On TM-15-07	
Asymmetrical Luminaire Types (Type I,II,III,IV)	B2 U0 G0
Quadrilateral Symmetrical Luminaire Types (Type V,Area Light)	B2 U0 G0

C Plane (°):0.0-180.0: 180.0  
Test Lab:  
Test Type: TYPE C  
Temperature:  
Operator:

Gamma Plane (°):0.0-90.0:1.0  
Test Device: CHL-6E  
Distance: 2.905 m  
Humidity:  
Inspector:



## Zonal Lumen

Gamma [°]	I <sub>mean</sub> [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
0.0-1.0	2440.7	2.3	2.3	0.14	0.14
1.0-2.0	2444.5	7.0	9.4	0.43	0.57
2.0-3.0	2452.0	11.7	21.1	0.71	1.28
3.0-4.0	2460.0	16.5	37.6	1.00	2.28
4.0-5.0	2467.1	21.2	58.8	1.29	3.58
5.0-6.0	2473.1	26.0	84.8	1.58	5.16
6.0-7.0	2477.6	30.8	115.5	1.87	7.03
7.0-8.0	2478.3	35.5	151.0	2.16	9.18
8.0-9.0	2472.4	40.1	191.1	2.44	11.62
9.0-10.0	2458.6	44.5	235.6	2.71	14.33
10.0-11.0	2434.8	48.7	284.2	2.96	17.29
11.0-12.0	2399.4	52.5	336.7	3.19	20.48
12.0-13.0	2352.7	55.8	392.5	3.40	23.88
13.0-14.0	2295.7	58.8	451.3	3.57	27.45
14.0-15.0	2228.9	61.2	512.5	3.72	31.17
15.0-16.0	2154.9	63.2	575.7	3.84	35.01
16.0-17.0	2075.7	64.6	640.3	3.93	38.95
17.0-18.0	1993.6	65.7	706.0	4.00	42.94
18.0-19.0	1909.3	66.4	772.5	4.04	46.99
19.0-20.0	1820.4	66.6	839.1	4.05	51.04
20.0-21.0	1726.4	66.3	905.4	4.03	55.07
21.0-22.0	1626.8	65.4	970.8	3.98	59.05
22.0-23.0	1520.7	63.8	1034.6	3.88	62.93
23.0-24.0	1409.1	61.6	1096.2	3.75	66.68
24.0-25.0	1292.9	58.8	1155.0	3.58	70.25
25.0-26.0	1174.4	55.4	1210.5	3.37	73.63
26.0-27.0	1054.7	51.6	1262.1	3.14	76.76
27.0-28.0	933.6	47.3	1309.3	2.88	79.64
28.0-29.0	814.3	42.6	1352.0	2.59	82.23
29.0-30.0	701.3	37.9	1389.8	2.30	84.54
30.0-31.0	596.9	33.2	1423.1	2.02	86.56
31.0-32.0	502.1	28.8	1451.8	1.75	88.31
32.0-33.0	417.0	24.6	1476.4	1.49	89.80
33.0-34.0	341.2	20.7	1497.0	1.26	91.06
34.0-35.0	275.3	17.1	1514.1	1.04	92.10
35.0-36.0	220.1	14.0	1528.2	0.85	92.95

C Plane (°):0.0-180.0: 180.0  
Test Lab:  
Test Type: TYPE C  
Temperature:  
Operator:

Gamma Plane (°):0.0-90.0:1.0  
Test Device: CHL-6E  
Distance: 2.905 m  
Humidity:  
Inspector:



## Zonal Lumen (Continue 1)

Gamma [°]	I <sub>mean</sub> [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
36.0-37.0	175.3	11.4	1539.6	0.70	93.65
37.0-38.0	139.1	9.3	1548.9	0.56	94.21
38.0-39.0	110.4	7.5	1556.4	0.46	94.67
39.0-40.0	89.0	6.2	1562.6	0.38	95.05
40.0-41.0	74.0	5.3	1567.9	0.32	95.37
41.0-42.0	63.4	4.6	1572.5	0.28	95.65
42.0-43.0	56.0	4.1	1576.7	0.25	95.90
43.0-44.0	50.6	3.8	1580.5	0.23	96.13
44.0-45.0	46.3	3.6	1584.0	0.22	96.35
45.0-46.0	42.8	3.3	1587.4	0.20	96.55
46.0-47.0	39.9	3.2	1590.5	0.19	96.74
47.0-48.0	37.3	3.0	1593.6	0.18	96.93
48.0-49.0	34.9	2.9	1596.4	0.17	97.10
49.0-50.0	32.7	2.7	1599.2	0.17	97.27
50.0-51.0	30.8	2.6	1601.8	0.16	97.43
51.0-52.0	29.0	2.5	1604.2	0.15	97.58
52.0-53.0	27.3	2.4	1606.6	0.14	97.72
53.0-54.0	25.9	2.3	1608.9	0.14	97.86
54.0-55.0	24.7	2.2	1611.1	0.13	97.99
55.0-56.0	23.6	2.1	1613.2	0.13	98.12
56.0-57.0	22.7	2.1	1615.3	0.13	98.25
57.0-58.0	21.8	2.0	1617.3	0.12	98.37
58.0-59.0	20.9	2.0	1619.3	0.12	98.49
59.0-60.0	20.2	1.9	1621.2	0.12	98.61
60.0-61.0	19.5	1.9	1623.0	0.11	98.72
61.0-62.0	18.7	1.8	1624.8	0.11	98.83
62.0-63.0	17.8	1.7	1626.6	0.11	98.94
63.0-64.0	17.0	1.7	1628.2	0.10	99.04
64.0-65.0	16.1	1.6	1629.8	0.10	99.13
65.0-66.0	15.1	1.5	1631.3	0.09	99.23
66.0-67.0	14.1	1.4	1632.8	0.09	99.31
67.0-68.0	13.1	1.3	1634.1	0.08	99.39
68.0-69.0	12.0	1.2	1635.3	0.07	99.47
69.0-70.0	11.0	1.1	1636.5	0.07	99.54
70.0-71.0	10.0	1.0	1637.5	0.06	99.60
71.0-72.0	8.9	0.9	1638.4	0.06	99.66

C Plane (°):0.0-180.0: 180.0  
Test Lab:  
Test Type: TYPE C  
Temperature:  
Operator:

Gamma Plane (°):0.0-90.0:1.0  
Test Device: CHL-6E  
Distance: 2.905 m  
Humidity:  
Inspector:



Gamma Plane (°):0.0-90.0:1.0  
Test Device: CHL-6E  
Distance: 2.905 m  
Humidity:  
Inspector:



## Candlepower Table

Unit: cd

G\C	C0.0	C180.0								
G0.0	2439.6	2439.6								
G1.0	2430.6	2452.8								
G2.0	2427.2	2467.5								
G3.0	2426.6	2486.6								
G4.0	2425.2	2501.6								
G5.0	2428.7	2512.8								
G6.0	2432.5	2518.5								
G7.0	2440.6	2518.8								
G8.0	2443.8	2510.0								
G9.0	2440.3	2495.4								
G10.0	2426.1	2472.6								
G11.0	2401.9	2438.7								
G12.0	2364.8	2392.1								
G13.0	2316.4	2337.6								
G14.0	2255.7	2273.1								
G15.0	2180.1	2206.7								
G16.0	2095.8	2137.1								
G17.0	2006.3	2063.6								
G18.0	1914.4	1990.3								
G19.0	1817.3	1915.1								
G20.0	1714.4	1834.7								
G21.0	1608.4	1748.0								
G22.0	1499.6	1651.3								
G23.0	1389.0	1543.1								
G24.0	1279.9	1424.3								
G25.0	1171.8	1295.6								
G26.0	1063.3	1167.0								
G27.0	950.7	1037.8								
G28.0	837.4	908.6								
G29.0	728.9	782.5								
G30.0	632.7	661.3								
G31.0	545.4	548.3								
G32.0	465.4	449.3								
G33.0	388.8	364.3								
G34.0	321.6	290.0								
G35.0	261.4	228.2								
G36.0	211.9	179.0								

C Plane (°):0.0-180.0: 180.0  
Test Lab:  
Test Type: TYPE C  
Temperature:  
Operator:

Gamma Plane (°):0.0-90.0:1.0  
Test Device: CHL-6E  
Distance: 2.905 m  
Humidity:  
Inspector:



## Candlepower Table (Continue 1)

Unit: cd

G\C	C0.0	C180.0								
G37.0	170.2	140.3								
G38.0	134.9	110.9								
G39.0	106.3	89.4								
G40.0	86.2	74.3								
G41.0	71.6	63.9								
G42.0	61.5	56.6								
G43.0	54.8	51.0								
G44.0	49.7	46.7								
G45.0	45.9	42.9								
G46.0	42.5	40.0								
G47.0	39.7	37.3								
G48.0	37.1	35.1								
G49.0	34.8	32.4								
G50.0	32.7	30.6								
G51.0	30.9	29.0								
G52.0	29.1	27.0								
G53.0	27.5	25.5								
G54.0	26.1	24.3								
G55.0	24.9	23.5								
G56.0	23.8	22.4								
G57.0	22.9	21.5								
G58.0	22.0	20.6								
G59.0	21.3	20.0								
G60.0	20.6	19.0								
G61.0	20.0	18.3								
G62.0	19.0	17.3								
G63.0	18.0	16.8								
G64.0	17.5	15.7								
G65.0	16.4	14.8								
G66.0	15.4	13.7								
G67.0	14.5	12.9								
G68.0	13.3	11.9								
G69.0	12.2	10.8								
G70.0	11.2	9.8								
G71.0	10.1	8.8								
G72.0	9.1	7.8								
G73.0	8.3	6.8								

C Plane (°):0.0-180.0: 180.0  
Test Lab:  
Test Type: TYPE C  
Temperature:  
Operator:

Gamma Plane (°):0.0-90.0:1.0  
Test Device: CHL-6E  
Distance: 2.905 m  
Humidity:  
Inspector:



Unit: cd

[illegible]

Inspector: